

## **MOTOR DATA SHEET**



06-05-2024

Motor type: 3SIE315S8

Series: IE3

	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	0	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	А	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	55	75	S1	107	740	710	1.9	2.6	6.3	91.4	92.5	92.5	0.63	0.75	0.80
690	Y	50	55	75	S1	62.1	740	710	1.9	2.6	6.3	91.4	92.5	92.5	0.63	0.75	0.80

GENERAL DATA						
Efficiency class	IE3	Sound pressure level [dB]	66			
Frame size	315	Sound power level [dB]	76			
Number of poles	8 Terminal box position		top			
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes			
Insulation class	F Bearing on D-side		6318C3			
Frequency converter supply	on demand	Bearing on ND-side	6318C3			
Mounting arrangement	IMB3/B5/B35 Bearings regreasing		yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	850	Feet - material	cast iron			
Moment of inertia [kgm2]	1.90	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	Ν			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	2 + 1	Winding heaters	on demand			
Temperature sensors in winding	3 x PTC	Optional accessories	on demand			

STANDARDS
IEC 60034-1

CERTIFICATES

on demand



As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2024 Cantoni Group www.cantonigroup.com