



MOTOR DATA SHEET

Motor type: **2SIE160L2**

Series: **IE2**

19-05-2024

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	18.5	25	S1	32.1	2935	60.2	2.3	2.9	7.7	92.1	92.3	91.5	0.82	0.89	0.91
690	Y	50	18.5	25	S1	18.6	2935	60.2	2.3	2.9	7.7	92.1	92.3	91.5	0.82	0.89	0.91

GENERAL DATA

Efficiency class	IE2	Sound pressure level [dB]	69
Frame size	160	Sound power level [dB]	82
Number of poles	2	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63092Z
Frequency converter supply	yes	Bearing on ND-side	63092Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	118	Feet - material	cast iron
Moment of inertia [kgm ²]	0.059	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand