CANTONI MOTOR



MOTOR DATA SHEET

Motor type: **PSg132M-4**

Series: **IE1**

28-03-2024

ELECTRICAL PARAMETERS

U	*CONN.*	*f*	*P*		*Duty*	*I*	*n*	*T*	*TL/T*	*TB/T*	*IL/I*	*Efficiency at load [%]*			*Power factor at load [-]*		
V	-	*Hz*	*kW*	*HP*	-	*A*	*rpm*	*N*	-	-	-	*2/4*	*3/4*	*4/4*	*2/4*	*3/4*	*4/4*
400	Δ	50	9.2	12.4	S1	18.5	1455	60.38	2.6	3.2	8.0	86.3	87.7	87.3	0.64	0.76	0.82
690	Y	50	9.2	12.4	S1	10.8	1455	60.38	2.6	3.2	8.0	86.3	87.7	87.3	0.64	0.76	0.82

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	62
Frame size	132	Sound power level [dB]	75
Number of poles	4	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Bearing on D-side	6308 2Z C3	Frequency converter supply	yes
Bearing on ND-side	6308 2Z C3	Mounting arrangement	IMB3/B5/B35
Bearings regreasing	on demand	Cooling method	IC411
Housing - material	cast iron	Weight (IMB3) [kg]	77.0
Feet - material	cast iron	Moment of inertia [kgm2]	0.043
Bearing shields - material	cast iron	Direction of rotation	CW/CCW
Painting	RAL5010	Degree of protection	IP55
Climatic execution	N		

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand

As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2024 Cantoni Group www.cantonigroup.com

Cantoni GROUP