CANTONI MOTOR



MOTOR DATA SHEET

Motor type: **PSh90L-4**

Series: **IE1**

29-03-2024

ELECTRICAL PARAMETERS

U	*CONN.*	*f*	*P*		*Duty*	*I*	*n*	*T*	*TL/T*	*TB/T*	*IL/I*	*Efficiency at load [%]*			*Power factor at load [-]*		
V	-	*Hz*	*kW*	*HP*	-	*A*	*rpm*	*N*	-	-	-	*2/4*	*3/4*	*4/4*	*2/4*	*3/4*	*4/4*
230	Δ	50	2.2	3.0	S1	9.1	1410	14.9	2.7	2.9	5.45	75.6	78.4	78.0	0.55	0.70	0.78
400	Y	50	2.2	3.0	S1	5.2	1410	14.9	2.7	2.9	5.45	75.6	78.4	78.0	0.55	0.70	0.78

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	61
Frame size	90	Sound power level [dB]	71
Number of poles	4	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6205 2Z C3
Frequency converter supply	yes	Bearing on ND-side	6205 2Z C3
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	19.4	Feet - material	aluminium
Moment of inertia [kgm2]	0.0034	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand

As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2024 Cantoni Group www.cantonigroup.com

Cantoni GROUP