CANTONI MOTOR



MOTOR DATA SHEET

Motor type: **SIE225M4-K**

Series: **IE1**

29-03-2024

ELECTRICAL PARAMETERS

U	*CONN.*	*f*	*P*		*Duty*	*I*	*n*	*T*	*TL/T*	*TB/T*	*IL/I*	*Efficiency at load [%]*			*Power factor at load [-]*		
V	-	*Hz*	*kW*	*HP*	-	*A*	*rpm*	*N*	-	-	-	*2/4*	*3/4*	*4/4*	*2/4*	*3/4*	*4/4*
400	Δ	50	45	60	S1	79	1480	290	2.6	2.3	7.0	93.9	94.3	94.0	0.80	0.86	0.88
690	Y	50	45	60	S1	46	1480	290	2.6	2.3	7.0	93.9	94.3	94.0	0.80	0.86	0.88

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	76
Frame size	225	Sound power level [dB]	86
Number of poles	4	Terminal box position	on right side
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6313C3
Frequency converter supply	yes	Bearing on ND-side	6313C3
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	345	Feet - material	cast iron
Moment of inertia [kgm2]	0.53	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2 + 1	Winding heaters	on demand
Temperature sensors in winding	3 x PTC	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand

As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2024 Cantoni Group www.cantonigroup.com

Cantoni GROUP