



MOTOR DATA SHEET

Motor type: **Sg160L-4**

Series: **IE1**

17-08-2022

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ	50	15	20	S1	27.8	1460	98.12	2.4	3.2	7.3	89.1	89.9	89.5	0.73	0.82	0.87
690	Y	50	15	20	S1	16.1	1460	98.12	2.4	3.2	7.3	89.1	89.9	89.5	0.73	0.82	0.87

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	66
Frame size	160	Sound power level [dB]	77
Number of poles	4	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63092Z
Frequency converter supply	yes	Bearing on ND-side	63092Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	125	Feet - material	cast iron
Moment of inertia [kgm ²]	0.075	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand