CANTONI MOTOR



MOTOR DATA SHEET

Motor type: **SIE225M6_4-K**

Series: **MULTI SPEED**

28-03-2024

ELECTRICAL PARAMETERS

U	*CONN.*	*f*	*P*		*Duty*	*I*	*n*	*T*	*TL/T*	*TB/T*	*IL/I*	*Efficiency at load [%]*			*Power factor at load [-]*		
V	-	*Hz*	*kW*	*HP*	-	*A*	*rpm*	*N*	-	-	-	*2/4*	*3/4*	*4/4*	*2/4*	*3/4*	*4/4*
400	Y	50	25	34	S1	52	990	241	3.0	3.1	7.8	86.7	87.7	87.5	0.63	0.74	0.79
400	Y	50	35	47	S1	62	1480	226	2.0	1.9	7.2	85.9	88.3	90.0	0.76	0.85	0.90

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	62|71
Frame size	225	Sound power level [dB]	72|81
Number of poles	6|4	Terminal box position	on right side
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6313P63E1
Frequency converter supply	on demand	Bearing on ND-side	6313P63E1
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight [kg]	365	Feet - material	cast iron
Moment of inertia [kgm2]	0.87	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2 + 1	Winding heaters	on demand
Temperature sensors in winding	yes	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand

As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2024 Cantoni Group www.cantonigroup.com

Cantoni GROUP