

## MOTOR DATA SHEET

Motor type: **SIE225S8\_6\_4-K**

Series: **MULTI SPEED**



30-04-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	16	21	S1	37.5	742	206	2.7	3.0	6.8	80.6	84.3	86.0	0.46	0.60	0.72
400	Y	50	20	27	S1	38.5	990	193	1.6	2.6	6.5	86.4	87.4	86.7	0.70	0.81	0.86
400	YY	50	26	35	S1	46	1482	168	1.8	2.8	7.7	86.4	88.0	88.1	0.82	0.89	0.93

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	58 63 73
Frame size	225	Sound power level [dB]	68 73 83
Number of poles	8 6 4	Terminal box position	on right side
Starting method	DOL / DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6313P63E1
Frequency converter supply	on demand	Bearing on ND-side	6313P63E1
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight [kg]	330	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.76	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	9	Temperature sensors in bearings	on demand
Cable glands/inlets	2 + 1	Winding heaters	on demand
Temperature sensors in winding	yes	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand