

## MOTOR DATA SHEET

Motor type: **Sg100L-6\_4A**

Series: **MULTI SPEED**



29-04-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	0.9	1.21	S1	2.9	960	8.95	1.75	2.6	4.2	55.2	62.4	65.5	0.48	0.60	0.70
400	Y	50	1.3	1.8	S1	3.5	1440	8.62	1.55	2.6	4.85	58.2	65.4	58.2	0.55	0.67	0.77

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	53 62
Frame size	100	Sound power level [dB]	78 81
Number of poles	6 4	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	62062Z
Frequency converter supply	on demand	Bearing on ND-side	62062Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight [kg]	21.5	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.0088	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand