

## MOTOR DATA SHEET

Motor type: **Sg160L-4\_2**

Series: **MULTI SPEED**



19-05-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	13	17.50	S1	25.1	1455	85.33	2.0	2.6	6.8	87.6	88.5	88.0	0.70	0.80	0.85
400	YY	50	16	21.4	S1	29.1	2915	52.42	2.0	2.7	7.6	83.8	86.1	86.4	0.86	0.90	0.92

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	65 82
Frame size	160	Sound power level [dB]	74 82
Number of poles	4 2	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63092Z
Frequency converter supply	on demand	Bearing on ND-side	63092Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand
Cooling method	IC411	Housing - material	cast iron
Weight [kg]	130	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.075	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand