

## MOTOR DATA SHEET

Motor type: **Sg160L-8\_4**

Series: **MULTI SPEED**



03-05-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	7.2	9.6	S1	19.4	720	95.5	2.1	2.9	5.6	80.2	83.5	83.9	0.43	0.55	0.64
400	YY	50	12	16.3	S1	22	1440	79.58	1.9	2.7	7.2	87.2	88.0	87.3	0.81	0.87	0.90

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	63 67
Frame size	160	Sound power level [dB]	70 79
Number of poles	8 4	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63092Z
Frequency converter supply	on demand	Bearing on ND-side	63092Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand
Cooling method	IC411	Housing - material	cast iron
Weight [kg]	130	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.096	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand