

## MOTOR DATA SHEET

Motor type: **Sh71-4\_2AW**

Series: **MULTI SPEED**



07-05-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	0.07	0.09	S1	0.3	1420	0.48	1.6	2	3.7	-	-	50.0	-	-	0.70
400	YY	50	0.28	0.37	S1	1.25	2800	0.96	1.6	1.8	3.2	-	-	50.0	-	-	0.70

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	-
Frame size	71	Sound power level [dB]	-
Number of poles	4 2	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	62032Z
Frequency converter supply	on demand	Bearing on ND-side	62032Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight [kg]	4.9	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.000606	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 54/IP 55	Climatic execution	U/2

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6		
-------------------------------	---	--	--

### STANDARDS

IEC 60034-1
-------------

### CERTIFICATES

on demand
-----------