

MOTOR DATA SHEET

Motor type: **Sh80-8_4AW**

Series: **MULTI SPEED**



06-05-2024

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	0.12	0.16	S1	0.7	670	1.71	1.5	1.9	2.3	-	-	45.0	-	-	0.78
400	YY	50	0.50	0.66	S1	1.4	1350	3.54	1.5	1.5	2.8	-	-	59.0	-	-	0.78

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	-
Frame size	80	Sound power level [dB]	-
Number of poles	8 4	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6204Z2
Frequency converter supply	on demand	Bearing on ND-side	6204Z2
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight [kg]	7.3	Feet - material	aluminium
Moment of inertia [kgm ²]	0.001693	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 54/IP 55	Climatic execution	U/2

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6		
-------------------------------	---	--	--

STANDARDS

IEC 60034-1

CERTIFICATES

on demand
