



MOTOR DATA SHEET

Motor type: **Sf315Y6-E**

Series: **STANDARD EFFICIENCY**

05-12-2024

| ELECTRICAL PARAMETERS | | | | | | | | | | | | | | | | | |
|-----------------------|-------|----|-----|-----|------|------|-----|------|------|------|------|------------------------|-----|------|--------------------------|-----|------|
| U | CONN. | f | P | | Duty | I | n | T | TL/T | TB/T | IL/I | Efficiency at load [%] | | | Power factor at load [-] | | |
| V | - | Hz | kW | HP | - | A | rpm | Nm | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 6000 | Y | 50 | 160 | 220 | S1 | 19.8 | 991 | 1542 | 2.2 | 2.1 | 5.9 | - | - | 94.8 | - | - | 0.82 |

| GENERAL DATA | | | |
|---------------------------------------|-------------|--------------------------------------|---------------|
| Efficiency class | - | Sound pressure level [dB] | - |
| Frame size | 315 | Sound power level [dB] | - |
| Number of poles | 6 | Terminal box position | on right side |
| Starting method | DOL | Possibility of terminal box rotation | yes |
| Insulation class | F | Bearing on D-side | 6320C3 |
| Frequency converter supply | on demand | Bearing on ND-side | NU320EM1 |
| Mounting arrangement | IM1001 (B3) | Bearings regreasing | yes |
| Cooling method | IC611 | Housing - material | steel |
| Weight (IMB3) [kg] | 1730 | Feet - material | steel |
| Moment of inertia [kgm ²] | 7.4 | Bearing shields - material | steel |
| Direction of rotation | CW/CCW | Painting | RAL5010 |
| Degree of protection | IP55 | Climatic execution | N |

| ENVIRONMENTAL CONDITIONS | | | |
|--------------------------|--------------------|------------------------------|------------|
| Ambient temperature [°C] | from -20 up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

| ACCESSORY | | | |
|--------------------------------|--------------------------|---------------------------------|--------------------------|
| Number of terminals or cables | 3 | Temperature sensors in bearings | 2 x Pt100 (1 pc/bearing) |
| Cable glands/inlets | 1 | Winding heaters | on demand |
| Temperature sensors in winding | 6 x Pt100 (2 pcs./phase) | Optional accessories | on demand |

| STANDARDS | |
|------------|--|
| IEC60034-1 | |

| CERTIFICATES | |
|--------------|--|
| on demand | |