



MOTOR DATA SHEET

Motor type: **Sh560H4C**

Series: **HIGH EFFICIENCY**

07-05-2024

ELECTRICAL PARAMETERS

| U | CONN. | f | P | | Duty | I | n | T | TL/T | TB/T | IL/I | Efficiency at load [%] | | | Power factor at load [-] | | |
|------|-------|----|------|------|------|-----|------|-------|------|------|------|------------------------|-----|------|--------------------------|-----|------|
| V | - | Hz | kW | HP | - | A | rpm | N | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 6000 | Y | 50 | 1800 | 2410 | S1 | 199 | 1494 | 11506 | 0.9 | 2 | 6.3 | - | - | 97.5 | - | - | 0.89 |

GENERAL DATA

| | | | |
|---------------------------------------|------------------------------------|--------------------------------------|-----------------------------|
| Efficiency class | - | Sound pressure level [dB] | 84 |
| Frame size | 560 | Sound power level [dB] | - |
| Number of poles | 4 | Terminal box position | top/ * side |
| Starting method | DOL | Possibility of terminal box rotation | yes |
| Insulation class | F | Bearing on D-side | NU230EM1+6230MC3 / *6232MC3 |
| Frequency converter supply | on demand | Bearing on ND-side | NU226EM1/*7332BMP |
| Mounting arrangement | B3/B35/V1* | Bearings regreasing | yes |
| Cooling method | IC411 | Housing - material | cast iron |
| Weight [kg] | 9020 | Feet - material | cast iron |
| Moment of inertia [kgm ²] | 119 | Bearing shields - material | cast iron |
| Direction of rotation | CW or CCW (according to the order) | Painting | RAL5010 |
| Degree of protection | IP55 | Climatic execution | N |

ENVIRONMENTAL CONDITIONS

| | | | |
|--------------------------|--------------------|------------------------------|------------|
| Ambient temperature [°C] | from -20 up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

ACCESSORY

| | | | |
|--------------------------------|--------------------------|---------------------------------|--------------------------|
| Number of terminals or cables | 3 | Temperature sensors in bearings | 2 x Pt100 (1 pc/bearing) |
| Cable glands/inlets | 1 | Winding heaters | on demand |
| Temperature sensors in winding | 6 x Pt100 (2 pcs./phase) | Optional accessories | on demand |

STANDARDS

| |
|-------------|
| IEC 60034-1 |
|-------------|

CERTIFICATES

| |
|-----------|
| on demand |
|-----------|