

MOTOR DATA SHEET

Motor type: **SIE405T4**

Series: **NEMA PREMIUM**



12-05-2024

ELECTRICAL PARAMETERS																	
U	CONN.	f	F	•	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460	Δ	60	75	100	cont.	108	1785	398.6	2.2	2.3	7.3	95.7	95.9	95.4	0.84	0.89	0.91

GENERAL DATA						
Efficiency class	NEMA PREMIUM	Sound pressure level [dB]	76			
Frame size	405	Sound power level [dB]	86			
Number of poles	4	Terminal box position	left side			
Starting method	DOL, PWS	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	6315C3			
Frequency converter supply	on demand	Bearing on ND-side	6315C3			
Mounting arrangement	IMB3/IMB35	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight [Lbs]	1241	Feet - material	cast iron			
Moment of inertia [Lb-Ft2]	29.8	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	12	Temperature sensors in bearings	on demand			
Cable glands/inlets	2	Winding heaters	on demand			
Temperature sensors in winding	3 x PTC	Optional accessories	on demand			

STANDARDS	
NEMA MG-1	

	CERTIFICATES
ſ	CSA

ADDITIONAL INFO					
NEMA design	В	NEMA code letter	G		

