

MOTOR DATA SHEET

Motor type: ESg215T-6



14-05-2024

Series: **NEMA EPACT**

	ELECTRICAL PARAMETERS																
U	CONN.	f	I	D	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	А	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460		60	3.7	5	cont.	6.6	1155		1.9	2.5	6.1	87.2	88.4	87.5			

GENERAL DATA						
Efficiency class	NEMA EPACT	Frame size	215			
Number of poles	6	Insulation class	F			
Frequency converter supply	on demand	Cooling method	IC411			
Direction of rotation	CW/CCW	Painting	RAL5010			
Climatic execution	Ν					

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Optional accessories on demand							
STANDARDS							
NEMA MG-1							
CERTIFICATES							

CSA

ADDITIONAL INFO							
NEMA code letter	Н						

As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright $\ensuremath{\mathbb{C}}$ 2024 Cantoni Group www.cantonigroup.com

