

MOTOR DATA SHEET

Motor type: ESg284T-4



14-05-2024

Series:	NEMA EPACT

	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	5	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Powe	r factor at l	oad [-]
V	-	Hz	kW	HP	-	А	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460		60	18.5	25	cont.	28	1760		2.3	2.3	6.2	93.2	93.2	92.4			

GENERAL DATA						
Efficiency class	NEMA EPACT	Frame size	284			
Number of poles	4	Insulation class	F			
Frequency converter supply	on demand	Cooling method	IC411			
Direction of rotation	CW/CCW	Painting	RAL5010			
Climatic execution	Ν					

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000			
Relative humidity [%]	up to 95					

ACCESSORY						
Optional accessories	al accessories on demand					
STANDARDS						
NEMA MG-1						
CERTIFICATES						

CSA

	ADDITIO	NAL INFO	
NEMA code letter	F		

As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.



