



MOTOR DATA SHEET

Motor type: **dSg180M4-EP**

Series: **GENERAL PURPOSE**

03-05-2024

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
1000	Y	50	18.5	25	S1	13.1	1465	121	2.3	2.9	6.9	90.3	90.9	90.8	0.82	0.88	0.9

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	68
Frame size	160	Sound power level [dB]	78
Number of poles	4	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	no
Insulation class	F	Bearing on D-side	63112Z
Frequency converter supply	on demand	Bearing on ND-side	63112Z
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no
Cooling method	IC411	Housing - material	cast iron
Weight [kg]	205	Feet - material	cast iron
Moment of inertia [kgm ²]	0.11	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 100		

ACCESSORY

Number of terminals or cables	3	Temperature sensors in bearings	1 x bimetal (D-side)
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	3 x bimetallic	Optional accessories	on demand

STANDARDS

IEC 60034-1, IEC 60079-0, IEC 60079-1

CERTIFICATES

ATEX, EAC, BiH

ADDITIONAL INFO

Ex marking	I M2 Ex db I Mb / II2G Ex db IIA T5 Gb	
------------	--	--