



MOTOR DATA SHEET

Motor type: **3SGf280M4-E**

Series: **FOR MINING CONVEYOR BELT DRIVES 3SGF SERIES**

04-05-2024

ELECTRICAL PARAMETERS																	
U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
500	Y	50	90	125	S1/S4	127	1480	582	2.3	2.2	5.5	94.1	94.3	94.0	0.81	0.86	0.87

GENERAL DATA			
Efficiency class	-	Sound pressure level [dB]	82
Frame size	280	Sound power level [dB]	92
Number of poles	4	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	no
Insulation class	F	Bearing on D-side	NU 317
Frequency converter supply	on demand	Bearing on ND-side	6317 C3
Mounting arrangement	IMB35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	steel
Weight [kg]	815	Feet - material	steel
Moment of inertia [kgm ²]	1.62	Bearing shields - material	cast iron
Direction of rotation	CW/CWW	Painting	RAL5010
Degree of protection	IP56	Climatic execution	N

ENVIRONMENTAL CONDITIONS			
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY			
Number of terminals or cables	3	Temperature sensors in bearings	2 x bimetallic (1pc/bearing)
Cable glands/inlets	2	Winding heaters	on demand
Temperature sensors in winding	3 x bimetallic	Optional accessories	on demand

STANDARDS	
IEC 60034-1, IEC 60079-0, IEC 60079-1, IEC 60079-7	

CERTIFICATES	
ATEX, EAC, BiH	

ADDITIONAL INFO		
Ex marking	IM2 Ex db I Mb	