



## MOTOR DATA SHEET

Motor type: **ExSg160L-2-2GT4**

Series: **INCREASED SAFETY**

09-05-2025

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	7.5	10	S1	13.1	2950	24.3	3.2	3.5	7.8	87.1	89.3	90.0	0.85	0.90	0.92

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	73
Frame size	160	Sound power level [dB]	84
Number of poles	2	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63092Z
Frequency converter supply	no	Bearing on ND-side	63092Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	129	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.058	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2	Winding heaters	no
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

EN 60079-0, EN 60079-15

### CERTIFICATES

ATEX

### ADDITIONAL INFO

tE heating time up to T4 temperature [s]	8	Ex marking	II 2G Ex eb IIC T4
--	---	------------	--------------------