



MOTOR DATA SHEET

Motor type: **ExSh56-4BT4**

Series: **INCREASED SAFETY**

02-05-2024

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	0.09	0.12	S1	0.37	1370	0.63	1.9	2.1	2.8	-	-	60.0	-	-	0.59

GENERAL DATA

Efficiency class	-	Frame size	56
Number of poles	4	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	62012Z
Frequency converter supply	no	Bearing on ND-side	62012Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight [kg]	3.2	Feet - material	aluminium
Bearing shields - material	aluminium	Painting	RAL5010
Degree of protection	IP66	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2	Winding heaters	no
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

EN 60079-0, EN 60079-31, EN 60079-7

CERTIFICATES

ATEX

ADDITIONAL INFO

tE heating time up to T4 temperature [s]	17	Ex marking	II 2G Ex eb T4 / II 2D Ex tb T125st.C
--	----	------------	---------------------------------------